



US Army Corps
of Engineers
Pittsburgh District

Notice to Navigation Interests

In reply refer to
Notice No. below

US Army Corps of Engineers, Pittsburgh District
1000 Liberty Avenue, Pittsburgh, PA 15222-4186
(412) 395-7650
<http://www.lrd.usace.army.mil/or/or-f/navrpt.htm>

Notice No. 12-16

Date: May 02, 2012

Dashiields Locks and Dam, Ohio River, Mile 13.3
Closure of the 110' x 600' Land Lock Chamber

1. **TO ALL WHOM IT MAY CONCERN:** Notice is given that the U.S. Army Corps of Engineers' Repair Party will close the 110' X 600' land lock chamber to repair the middle wall bullnose, replace miter gate fenders, and to install a new interlock system. The repair work is scheduled to begin at 1:00 AM on June 4, 2012 and will be completed by 11:00 PM on June 22, 2012.
2. The 110' x 600' lock chamber will be closed to traffic during this work period. The small chamber 56' x 360' will be available to navigation during this period. Major delays to navigation are expected.
3. This closure is required to install an upgraded interlock system on the locks control system. The interlock system is designed to prevent inadvertent and unsafe gate and valve operation that has resulted in catastrophic events at other Ohio River Locks. In addition, repairs will be made to the miter gates and upstream bullnose armor due to general wear and deterioration.
4. The Corps will institute the following lockage procedure which has been developed in cooperation with the Waterways Association of Pittsburgh. Boat locking order will be determined by arrival time at Dashiields L/D, all pilots should radio Dashiields L/D at normal arrival points. All red flag barges in the tow must also be reported by the pilot during this radio call. No adding or swapping of barges will be allowed once the tow's lock turn has been established. All tows must be ready to lock when put on the waiting list. The lockages will be accomplished as a standard series of three tows in one direction. Because of approach conditions (outdrafts and short river guard walls), it is recommended that users limit their tow size to no more than a triple lockage. **Under normal river conditions the Lockmaster will allow, if requested by the pilot when calling for position of the tow, a towboat to lock through with a maximum of five (5) lockages. In no case will the first or last tow in a series of**

three tows be more than a four (4) cut lockage unless only larger tows are in line. By following this procedure, there will be a minimal tow make-up and approach time when changing directions without a program of "self-help" by navigation interests, the Corps can only handle up to a triple lockage with its on-site tow haulage equipment.

5. To help eliminate some of the waiting time for towboats, an arriving tow can designate to be broken up into a maximum of three (3) separate tows. Each tow will then be locked in accordance with the procedure outlined in paragraph 4 above. The pilot of the large tow will have to notify Dashields L/D of the intent to breakup into smaller tows and must provide the Lockmaster with the names of the other towboats designated to handle the other tows not later than six (6) hours before their lockage turn. If the designated towboat(s) are not available when called by Dashields L/D, they will lose their turn and go to the end of the waiting line.

6. During the closure of the 110' x 600' lock chamber, tows should move to the closest mooring cell for staging prior to their lockage turn, rather than waiting at landings. Then it will be necessary for tows, under normal river conditions, to follow one another on the river guard wall when a series of lockages are being made in one direction. Each tow in the series should be aware of the tow that they follow and be on the river guard wall as soon as that tow enters the lock chamber. While this practice will speed up the lockage process, it is imperative that tows exercise extreme caution when encountering outdraft or backlash conditions.

7. In an effort to reduce delay time at the locks, a program of "self-help" by navigation interests is necessary. A "self-help" program will allow waiting towboats to assist tows out of the lock chamber. The Lockmaster will designate the helper boats as tows arrive for position. The second and third towboats in the first series of lockages in the opposite direction will be the designated helper boats unless conditions, equipment or cargo prevent the use of that towboat as a helper. Any tow with a tank barge must be accompanied at all times by a towboat. It will be necessary for all towboats to monitor their radios 24 hours a day.

8. Other specific procedures to facilitate lockage operations through the small chamber have been developed in cooperation with the towing industry. The Corps is asking for everybody's

cooperation and help in making the locking operations go as smoothly as possible during the closure of the large chamber.

a. All excess rigging will be removed prior to entering the lock chamber. Remaining rigging should be ready to be knocked loose after the cut is secured in the lock chamber.

b. **On upbound tows, two locking lines, one head and one stern, must be available on each cut. On downbound tows, two locking lines, one head and one stern, must be available on each cut.** Each line must be at least 75 feet long and 1-1/2" in diameter. To minimize locking time, all lines will stay with each cut. Lines will not be permitted to be carried from one cut to another.

c. **Three deckhands are required during multiple lockages.**

d. All multiple cut tows will be made up in designated staging areas, clear of the lock gates, so as not to interfere with lockage operations.

e. The Dashields lock filling system may cause turbulence and surging of water while filling the small chamber. **Deckhands need to be extra vigilant in tending lines to avoid an accident which could close the locks totally.**

9. Towboats are cautioned to use minimal power when operating over the lower sill to avoid forcing debris onto the miter sill. This debris could prevent the miter gates from closing and require stoppage of navigation until the material is removed by dredging or diving operations.

10. If critical industrial shipments are essential to sustain continued operation, the affected companies should immediately contact the Waterways Association of Pittsburgh. They will review all requests for priority before submitting them to the Corps for our consideration. If it becomes necessary to prioritize lockages through the small chamber, the Corps will make the final decision concerning lockage procedures as conditions and situations change. In accordance with standard Corps policy, the Lockmaster may also vary the locking procedure in an effort to equalize waiting times.

11. **Information concerning lockages will be broadcast by radio on Channel 13 and any towboat not answering a call from the locks will be dropped to the end of the waiting list.**

CELRP-OP
Navigation Notice No. 12-16

12. All towboats are to stay with their tows while waiting for lockages unless designated to assist other tows through the small lock.

FOR THE DISTRICT ENGINEER:

//Signed//
James R. Fisher
Chief, Operations Division